



PC SERIES GRANULATORS

1800 441 100

WASTEINITIATIVES.COM.AU



PC Series GRANULATORS

The PC Series granulators are designed for the volume reduction and sizing of various materials.

To suit different applications and improve efficiency of granulating different materials, a selection of different rotor configurations are available.

Optional extras are available including bagging units for outfeed and sound-proof enclosures to reduce operating noise emissions.

For ease of changing knives, maintenance and repairs, the hopper is designed to be easily and ergonomically tilted, ensuring safe and quick access.

BENEFITS

- Sound-proof enclosure
- Reliable & durable construction
- Easy maintenance
- Suitable for processing multiple products
- Safe & easy operation
- Variety of screen sizes available

APPLICATIONS

A wide variety of applications include:

- Plastic Film
- PVC Pipe
- Paper
- E-Waste
- Rubber
- Cables
- Plastic Drums
- Plastic Bottles



FEATURES THAT GUARANTEE **HIGH PERFORMANCE**

KEY FEATURES



Sizing Screen

Output product size is controlled by means of a changeable sizing screen. A selection of screen sizes are available.



Rotor

The rotor design incorporates a series of knives made from hardened D2 steel, which are designed to handle the harshest grades of plastic material and provide consistent performance.



Sound-Proof Enclosure

Sound-proof enclosures reduce granulator noise level considerably, enabling the machine to be operated in a broad range of applications where noise pollution may be a concern.



Safety Controls

Certified to Australian standards, interlocked safety doors and equipped with emergency stops.

ROTORS



Front Set V-Rotor

This rotor is our standard rotor, suitable for processing a wide range of materials at high speed. Materials include plastics, wood, paper, fibre and cable.



Rear Set V-Rotor

Similar to the front-set V-Rotor, this rotor configuration with the blades set at a high incline angle, lends itself very well to processing lighter materials such as bottles and pipe.



F-Rotor

The F-Rotor blades are mounted on the shaft in a staggered angle configuration, which helps reduce the impact during granulation. It is specifically designed for processing flexible materials such as PET bottles.



Ladder Blade Rotor

An extension of the F-Rotor blade configuration. The Ladder Blade Rotor is a high-inertia design which minimises the impact on each individual blade and is well suited to processing rigid and high-density materials.



L-Rotor

The L-Rotor is ideally suited to processing rubber material with optimum throughput and maximum cutting efficiency.



SPECIFICATIONS

Model Item	Dimension L/W/H (mm)	Cutting Chamber L/W (mm)	Main Shaft Speed (r/min)	Rotor-knive (PCS)	Main Motor Power (KW)	Weight (KG)
PC2660	1483 x 1328 x 1740	634 x 437	591	3 x 2	15	890
PC3260	1486 x 1368 x 1711	634 x 360	438	3 x 2	15	1485
PC3280	1586 x 1568 x 1814	834 x 414	627	3 x 2	22	1646
PC4280	1770 x 1642 x 2425	834 x 540	466	3 x 2	37	2820
PC42100	1770 x 1842 x 2425	1034 x 540	466	3 x 2	45	3230
PC42120	1760 x 2221 x 2530	1234 x 540	462	3 x 2	55	3650
PC52100	2119 x 2025 x 2984	1034 x 708	462	5 x 2	55	4200
PC52120	2070 x 2225 x 2984	1234 x 705	462	5 x 2	75	5300
PC66120	2410 x 2320 x 4340	1234 x 1080	462	5 x 2	90	7650
PC66160	2335 x 2808 x 4337	1634 x 1080	414	5 x 4	132	9720
PC80160	3000 x 2900 x 4763	1634 x 1000	414	7 x 4	200	11400
PC80200	2735 x 3373 x 4564	2033 x 1000	420	9 x 4	200	13600

*Please note: Specifications are indicative only and may be subject to change without notice. Equipment is sold with an operation manual and risk assessments relating to the equipment as supplied. It is the responsibility of the purchaser to conduct their own assessments and determine the suitability of the equipment for the intended use. Other models and custom builds available on request.