



WASTEPAC

HORIZONTAL BALERS

1800 441 100

WASTEINITIATIVES.COM.AU



OPTIMUM PERFORMANCE

WASTE PAC HORIZONTAL BALERS

Waste Initiatives "WastePac" range of Horizontal Balers are built to comprehensively meet the needs of the Australian market.

Our balers are designed for industrial applications and are built for maximum performance and longevity.

Waste Initiatives has the solution for:

- Fully-Automatic Horizontal Balers
- Semi-Automatic Horizontal Balers
- Two-Ram
- 3-Ram and Special Purpose Balers
- Conveyor Feed Systems
- Complete Turnkey Plants

BENEFITS

- Low energy consumption
- Reliable & durable construction
- Low maintenance
- Suitable for multiple products
- Safe & easy usage. Touchscreen operator interface
- Automatic feeding, baling & tying options

APPLICATIONS

A wide variety of applications include:

- Cardboard (OCC)
- Drink Bottles (PET)
- Milk Bottles (HDPE)
- Bulk Bags (PP)
- Shredded Paper
- MSW/RDF
- Aluminium Cans
- TV Casings
- Tyres
- Newsprint



FEATURES THAT GUARANTEE **HIGH PERFORMANCE**

KEY FEATURES

- Automatic start
- Bale exit table
- Long Life Low Noise(60 dB)
- Hopper view door
- Power save – auto sleep mode
- Touchscreen operator interface
- Automatic tie-off
- Variable bale length setting
- Multi-product settings
- Continuous feed
- Automatic bale counter
- Hour counter
- Emergency alarm

OPTIONAL EXTRAS

- De-jamming cylinders
- Operating signals
- Remote operating controls
- Replaceable Hardox shear knife
- Replaceable Hardox wear plates
- In-hopper pre-shredder
- Custom feed hopper
- Feed conveyor



AUTOMATIC BALE COUNTER



AUTOMATIC TIE-OFF



EMERGENCY STOP



TOUCHSCREEN INTERFACE



DE-JAMMING CYLINDERS



CUSTOM FEED HOPPER



BALE EXIT TABLE



FEED CONVEYOR



HOPPER VIEW WINDOW



HIGH RELIABILITY

SPECIFICATIONS

Model	Max Force	Motor Power	Bale size (WxHxL)	Main RAM cycle time	Number of Ties	Hopper Opening (mm)	Length (mm)	Width (mm)	Height (mm)	Weight (T)
Fully Automatic Balers										
Super40/50	40/50T	15/20Hp	700 x 700mm x variable	18 sec	3	900 x 630	6000	3250	4000	11
Super75	70T	18.5kW	1100 x 750mm x variable	23 sec	4	1450 x 1020	6696	4420	3800	13
Super90	89T	30kW	1100 x 750mm x variable	19 sec	4	1650 x 1020	7760	4420	4290	14
Super100	99T	37kW	1100 x 750mm x variable	20 sec	4	1700 x 1020	8740	4420	4270	15
Super125	125T	55kW	1100 x 1100mm x variable	26 sec	5	1850 x 1020	9750	4420	5000	16
Super150	150T	75kW	1100 x 1100mm x variable	13.5 sec	5	1850 x 1050	12000	5700	6000	39
Super190	190T	2 x 90kW	1100 x 1100mm x variable	12 sec	5	1920 x 1050	12000	5700	6000	42
Two Ram Balers										
TR130	133T	55kW	1070 x 780 x 1500mm	14-24 Sec	Variable	1700 x 1070	9000	4500	3500	20
TR200	185T	75kW	1070 x 780 x 1500mm	18-27 Sec	Variable	2000 x 1070	9600	4500	3500	27
Semi-Automatic Balers										
CD60SA	60T	18.5kW	1100 x 750 x 1200mm	42-44 Sec	4	1300 x 1100	6250	1300	2250	6
CD1111	100T	22kW	1050 x 1050 x 1750mm	45 Sec	5	1750 x 1000	8600	1750	2350	10

*Please note: Specifications are indicative only and may be subject to change without notice. Equipment is sold with an operation manual and risk assessments relating to the equipment as supplied. It is the responsibility of the purchaser to conduct their own assessments and determine the suitability of the equipment for the intended use. Other models and custom builds available on request.