

The Eagle Punch Cutter II is a mobile cutter designed to split off-the-road (OTR) tyres by cutting through the centre of the tread. It handles tyres from 39 inch rims to 14 foot diameters.

This unit offers manual and automatic modes, making 5-6 inch cuts with a 10 inch blade on a rotating turntable. For large OTR tyres, it completes the process in 10-12 minutes. This process is essential for thick rubber tyres like the 70/70/57, which can have up to 14 inches of solid rubber in the shoulder.



## Features

- Four hydraulic-powered bed rollers
- Durable heat-treated alloy punch blade
- Punch cuts up to 8 inches per operation
- Hydraulically adjustable tire cage
- PLC automatically turns the tire and punches
- Max. Tyre Capacity: 70/70-57

## Options

- Power options of Diesel or gas
- Automated radio remote control

## Specifications

### Punch Cutter II

<b>Power</b>	Kubota 38 HP turbo Diesel
<i>Optional</i>	25 HP Electric Motor 3 phase
Weight	12 020 kg
Weight on tongue	1 424 kg
Weight on rear axles	9 026 kg
Travel Height	4 115 mm
Work Height	5 588 mm
Travel Width	2 438 mm
Work Width	5 308 mm
Travel Length	6 930 mm
Work Length w tow	9 600 mm
Axles	Tandem, dual tyres
Blade size	10"
Outriggers	Two hydraulic outriggers and two manual outriggers
PLC	Automatically turns tyres and punches
Min. Tyre Capacity	3300/R51
Max. Tyre Capacity	Up to and including 70/70
Cycle Time	4-5 OTR tyres per hour

